



ORANGE ACTION

DELIMONENE CITRUS BASED DRAIN MAINTAINER



DESCRIPTION:

Naturally powerful citrus solvent cleaner/degreaser removes grease, tar, oil, & gum. Great lift station cleaner.

APPLICATIONS:

USE ON	USE IN	USE FOR
<ul style="list-style-type: none"> TAR OIL GRAFFITI GREASE ENGINES 	<ul style="list-style-type: none"> SEWER PLANTS LIFT STATIONS DUMPSTERS KENNELS SEPTIC TANKS 	<ul style="list-style-type: none"> CLEANING DEODORIZING DRAIN MAINTENANCE DELOGGING WAREHOUSE OPERATIONS

FEATURES & BENEFITS:

- Declogs and deodorizes grease traps and drains
- Wipes out grease and grime on a wide variety of surfaces
- Fantastic, naturally fresh citrus scent
- Non-acid, non-caustic, non-corrosive, and non-toxic
- 100% Natural • Biodegradable • Phosphate Free • No Petroleum Distillates

DIRECTIONS:

DIRECTIONS - HOW TO USE:

GREASE TRAPS, DRAIN MAINTENANCE AND DELOGGING: Add 8 oz. weekly to all drain openings and let stand 10 minutes flush with warm water. For grease traps under 20 cu. ft., add 5 oz. daily. Use more for larger traps. For clogged drains, pour 12 to 16 oz. into drain.

FOR GENERAL CLEANING and DEODORIZING: Dilute 4 to 8 oz. of concentrate per gallon of warm water. Sponge or spray onto surface and allow to stand a few moments. Wipe with clean cloth or sponge, rinse well.

FOR SEWER PLANT LIFT STATION CLEANING AND DEGREASING: Add 2-3 gallons directly to area on at least a weekly basis. To deodorize, see odor control directions below.

MACHINERY, ENGINES, RUBBER BURNS, GRAFFITI and HEAVY INDUSTRIAL CLEANING: Dilute concentrate 16 oz. per gallon of warm water. Mop, spray or sponge onto surface and allow to stand at least 5 minutes. Scrub or brush thoroughly and rinse with clean water.

TAR, ASPHALT & ADHESIVE REMOVAL: Apply concentrate directly. Wait 2 to 4 minutes, agitating if necessary. Rinse with clear water.

FOR ODOR CONTROL AROUND DUMPSTERS, GARBAGE DISPOSALS, SEPTIC TANKS, KENNELS, ETC.: Dilute 4 ounces of

concentrate per gallon of water. Spray or mop onto area to be treated and allow to stand. Around sewage treatment plants apply by the drip method or fogging. Product may be sprayed or fogged into the air if desired. **RUG AND UPHOLSTERY SPOT REMOVAL:** Apply concentrate with cloth to affected area and blot. For gum removal, blot directly on gum. Allow to work 2 -3 minutes. Use a scraper to remove gum.

ALWAYS TEST ON AN INCONSPICUOUS AREA OF FABRIC BEFORE APPLYING.

SPECIFICATIONS:

Physical state : Liquid
 Colour : orange
 Odour : Citrus fruits
 Odour threshold : No data available
 pH : No data available
 Melting point : No data available
 Freezing point : No data available
 Boiling point : 310
 Flash point : 145
 Relative evaporation rate (butylacetate=1) : No data available
 Flammability (solid, gas) : No data available
 Explosive limits : No data available
 Explosive properties : No data available
 Oxidising properties : No data available
 Vapour pressure : No data available
 Relative density : 0.85
 Solubility : Water: Solubility in water of component(s) of the mixture :

PACKING INFORMATION:

Available in Qts (12 pack), 5 gal pail, and 55 gal drum